

# CONVENTIONAL DETECTORS FOR FLAMESTOP FIRE ALARM PANELS



|                    |   |
|--------------------|---|
| <b>Part Number</b> | PHC-9102  |
| <b>Description</b> | 'FlameStop' Conventional Photo Optical Smoke Detector.  |
|                    | <ul style="list-style-type: none"> <li>• Aesthetically pleasing low profile design.</li> <li>• Twin LED for 360° vision.</li> <li>• Remote indicator output.</li> <li>• Removable chamber for easy cleaning and maintenance.</li> </ul> |
| <b>Dimensions</b>  | 100 x 50mm W x H  |

| Part Number        | Type  |
|--------------------|---|
| PHC-9103           | TYPE A HEAT DETECTOR  |
| PHC-9103-58FT      | TYPE B HEAT DETECTOR  |
| PHC-9103-74DHT     | TYPE C HEAT DETECTOR  |
| PHC-9103-74FT      | TYPE D HEAT DETECTOR  |
| <b>Description</b> | 'FlameStop' Conventional Heat Detector.   |
|                    | <ul style="list-style-type: none"> <li>• Fixed temperature &amp; rate of rise heat detection.</li> <li>• Aesthetically pleasing low profile design.</li> <li>• Twin LED for 360° vision.</li> <li>• Remote indicator output.</li> </ul> |
| <b>Dimensions</b>  | 100 x 50mm W x H  |



|                    |   |
|--------------------|---|
| <b>Part Number</b> | PH-DZ03   |
| <b>Description</b> | 'FlameStop' Detector Base for Conventional Detectors.   |
|                    | <ul style="list-style-type: none"> <li>• Base for termination and fixing of detectors.</li> <li>• Non-electronic component.</li> <li>• Common base for PHC-9102 and PHC-9103.</li> <li>• Remote indicator connections.</li> <li>• Optional tamper screw can be installed to prevent the detectors being removed from their base.</li> </ul> |
| <b>Dimensions</b>  | 104 x 13mm W x H  |

|                    |   |
|--------------------|---|
| <b>Part Number</b> | PHC-885WP   |
| <b>Description</b> | SYSTEM SENSOR MODEL 885WP-B Type B Sealed Heat Detector with Base   |
|                    | <ul style="list-style-type: none"> <li>• System Sensor Brand</li> <li>• Ideal for use in wet or high humidity areas</li> <li>• Sealed against entry of moisture (IP67)</li> <li>• Type B 63°C fixed temp operation</li> </ul> |