

Dräger X-am[®] 2500 Multi-Gas Detection

The Dräger X-am[®] 2500 was especially developed for use as personal protection. The 1 to 4 gas detector reliably detects combustible gases and vapours, as well as O₂, CO, NO₂, SO₂ and H₂S. Reliable and fully mature measuring technology, durable sensors and easy handling guarantee a high degree of safety with extremely low operating costs.



Benefits

Durable electrochemical sensors

Fully developed, high performance Dräger sensors in an extra small format for CO, H₂S, O₂, SO₂ and NO₂ gases enable safe use in industry, mining and in refineries. The impressive hydrogen sulphide sensor has a high resolution, so it can reliably measure even very low workplace limits. The non-consumptive and lead-free sensor for oxygen is characterized by an especially long service life of more than 5 years. Our CO and H₂S sensors also have this long service life expectation, so they contribute to especially low operating costs.

Poison resistant ex sensor

The innovative, catalytic Ex sensor is impressive due to its high resistance to silicone and hydrogen sulphide. Together with the high degree of drift stability, this resistance enables an extraordinarily long service life of more than 4 years. Its sensitivity with regard to flammable gases and vapours is tested in accordance with the technical approval for measuring IEC/EN 60079-29-1 from methane to nonane. This approval also demonstrates the suitability of this instrument for primary explosion protection, e.g. for use in refineries and in the chemical industry.

Maximum safety

The Dräger X-am 2500 has Ex approval for zone 0, so it is clearly designed for very high user safety in areas subject to explosion hazard. The functional design ensures that gas can enter from above and from the side – even if the instrument is inside a pocket or if the front gas entry is accidentally covered.

Maintenance: fast, easy, inexpensive

From functional test to complete documentation, users have access to practical solutions that provide safety for implementation at any time. The Dräger Bump Test Station, which does not require a local power source, and the automatic Dräger X-dock testing and calibration station for comprehensive equipment management are ideal system additions that save time and effort. Together with the Dräger X-dock, the high quality Dräger sensors enable quick bump tests of 8 to 15 seconds¹ with very low gas consumption. This significantly reduces your equipment operating costs.

1) With standard sensors: CH₄, O₂, CO, H₂S

Diffusion or pump

For clearance measurements for tanks and shafts or when searching for leaks, an optional external pump with a hose up to 30 m long is the optimum solution. The pump starts automatically when the measuring instrument is inserted in the external pump. The switch from diffusion to pump operation can be handled quickly and easily without tools or screws.

Benefits

Ergonomic and robust

Thanks to its low weight and ergonomic design, the Dräger X-am 2500 offers a high degree of wearing comfort. The practical two button control panel and easy menu navigation allow the instrument to be used intuitively, despite its comprehensive functionality. The integrated protective rubber coating and sensors that are not sensitive to shock provide additional safety in case of impacts or vibrations. More-over, the Dräger X-am 2500 is not sensitive to electromagnetic radiation, e.g. from wireless devices. The Dräger X-am 2500 is water and dust resistant in accordance with protection class IP67, so it remains fully functional even if it falls into the water.

Reliable power supply

The Dräger X-am 2500 can operate with either alkaline batteries or with rechargeable NiMH batteries. This enables a reliable power supply for more than 12 hours, and with the high capacity battery pack more than 13 hours. Depending on the requirements, the batteries can be charged either in the workshop or in a vehicle. Operating time without Ex sensor is typically more than 250 hours.

System components



D-47907-2012

Dräger X-dock® 5300/6300/6600

The Dräger X-dock® series provides you with full control of your portable Dräger gas detection instruments. Automatic bump tests and calibrations with reduced test gas consumption and short testing times save time and money. Comprehensive documentation and evaluations provide you with a clear overview.

System components



ST-740-2006

Dräger Bump Test Station

Easy to use, stand-alone and portable. With the Bump Test Station, functionality tests of gas detection and warning devices can be carried out easily and quickly.

Accessories



ST-9477-2007

Dräger X-am 125, external pump

External pump for hose length of up to 30 meters (98 feet). Makes it possible to use the detector for pre-entry measurements into confined spaces such as tanks, shafts, etc. The pump starts automatically when the detector is inserted. The change between diffusion and pump operation is quickly and easily possible without any need for additional tools or steps.



D-12284-2009

Power pack & Charging set

Consisting of: NiMH power supply, charging module, single charger

Related Products

ST-9466-2007



Dräger X-am® 5000

The Dräger X-am® 5000 belongs to a generation of gas detectors, developed especially for personal monitoring applications. This 1- to 5-gas detector reliably measures combustible gases and vapors as well as O₂ and harmful concentrations of toxic gases, organic vapors, Odorant and Amine.

D-27784-2009



Dräger X-am® 5600

Featuring an ergonomic design and innovative infrared sensor technology, the Dräger X-am 5600 is the smallest gas detection instrument for the measurement of up to 6 gases. Ideal for personal monitoring applications, this robust and water-tight detector provides accurate, reliable measurements of explosive, combustible and toxic gases and vapors as well as oxygen.

ST-67-2006



Dräger X-am® 7000

Dräger X-am® 7000 is the solution for the simultaneous and continuous measurement of up to five gases. It is the ideal companion in a variety of applications where the reliable detection of oxygen, toxic and combustible gases and vapors are necessary.

Technical Data

Dimensions (W × H × D)		48 × 130 × 44 mm
Weight		220 – 250 g
Ambient conditions	Temperature	-20 to +50 °C
	Pressure	700 to 1,300 mbar
	Relative humidity	10 to 95 % r.h.
Protection class		IP67
Alarms	Visual	360°
	Audible	Multi-tone > 90 dB at 30 cm
	Vibration	
Operating times		> 12 h with alkaline and NiMH, > 13 h with NiMH HC, > 250 h w/o Ex sensor with alkaline batteries
Charging time		< 4 h
Datalogger		Retrievable using an infrared interface > 1,000 h with 4 gases at a recording interval of 1 value per minute
Approvals	ATEX	I M1 Ex ia I Ma, II 1G Ex ia IIC T3 Ga, I M2 Ex d ia I Mb, II 2G Ex d ia IIC T4/T3 Gb
		Performance approval to:
	EN 50104 (2002) + A1(2004)	O ₂
	EN 45544	CO & H ₂ S
	EN 60079-29-1:2007	Methane to nonane
	EN 50271:2010	Software and documentation
	CSA (Canada & USA)	Class I Div. 1 Group A, B, C, D T.-Code T4/T3 A/Ex ia IIC T3 /Ga A/Ex d ia IIC T4/ T3 /Gb
IECEX	Ex ia I Ma Ex ia IIC T3 Ga Ex d ia I Mb Ex d ia IIC T4/ T3 Gb	
CE mark	Electromagnetic Compatibility (Directive 2004/108/EC); ATEX (Directive 94/9/EC)	
MED	Marine Equipment Directive (Directive 96/98/EC)	

Ordering Information

Dräger X-am® 2500	Order No.
Dräger X-am® 2500 - Available in various versions. Cannot be modified later with other sensors. Includes calibration certificate. No power supply included.	
Dräger X-am® 2500 EX ¹⁾	83 23 910
Dräger X-am® 2500 Ex, O ₂ ¹⁾	83 23 912
Dräger X-am® 2500 Ex, O ₂ , H ₂ S-LC ¹⁾	83 23 914
Dräger X-am® 2500 Ex, O ₂ , CO ¹⁾	83 23 916
Dräger X-am® 2500 Ex, O ₂ , H ₂ S-LC, CO ¹⁾	83 23 918
Dräger X-am® 2500 Flex ¹⁾	83 23 900
Choice of four sensors (1 slot for CatEx and 3 slots for XXS sensors). Can be modified later with other sensors. Includes calibration certificate. No power supply included.	

Ordering Information

DrägerSensors	Measuring range	Resolution	Response time(t ₉₀)	Expected service life	
CatEx 125 PR ¹⁾	0 – 100 % LEL 0 – 5 Vol.-% CH ₄	1 % LEL	10 sec.	> 4 years	68 12 950
CatEx 125 Mining PR	0 – 100 % LEL 0 – 100 Vol.-% CH ₄	1 % LEL	10 sec.	> 3 years	68 13 080
DrägerSensor XXS O ₂ 1)	0 – 25 Vol.-%	0,1 Vol.-%	10 sec.	> 5 years	68 10 881
DrägerSensor CO ¹⁾	0 – 2,000 ppm	2 ppm	15 sec.	> 5 years	68 10 882
DrägerSensor XXS H ₂ S LC ¹⁾	0 – 100 ppm	0,1 ppm	15 sec.	> 5 years	68 11 525
DrägerSensor NO ₂	0 – 50 ppm	0,1 ppm	15 sec.	> 3 years	68 10 884
DrägerSensor SO ₂	0 – 100 ppm	0,1 ppm	15 sec.	> 3 years	68 10 885

¹⁾ Dräger provides a 3 year guarantee on the Dräger X-am® 2500 and these sensors.

The legal rights arising from defects remain unaffected.

Power supply units

NiMH power pack T4 with charging module and PSU (complete set)	83 18 785
NiMH power pack T4	83 18 704
NiMH HC power pack T4 with charging module and PSU (complete set)	83 22 785
NiMH HC power pack T4	83 22 244
Alkaline power pack (w/o batteries)	83 22 237
Alkaline batteries T4 (2 pcs.) for power pack	83 22 240

Charging accessories

Charging module	83 18 639
Charging kit consisting of a charging module and a single charger (worldwide)	83 20 333
Power pack with power cord (worldwide) for multiple charging modules (max. 20)	83 15 805
Single charger (worldwide) for multiple charging modules (max. 5)	83 16 994
Single charger (worldwide) for multiple charging modules (max. 2)	83 15 635
Vehicle charging cable 12 V / 24 V for charging module	45 30 057
Vehicle mounting kit for a Dräger X-am® 1/2/5x00 charging module	83 18 779

Pump accessories

Dräger pump X-am® 125, external pump	83 19 400
Manual pump adapter	83 19 195
Confined Space Entry Kit with external pump and 3 m Viton® hose	83 19 399
Empty case with room for X-am® 1/2/5x00, charging accessories, probe, gas cylinder, pump, 3 m hose, etc.	83 20 467

Ordering Information

Calibration accessories

Calibration cradle for Dräger X-am® 1/2/5x00	83 18 752
Dräger X-dock® 5300 for Dräger X-am® 1/2/5x00	83 21 880
Other versions of Dräger X-dock®	by request
Dräger Bump Test Station for Dräger X-am® 1/2/5x00 (w/o gas cylinder)	83 19 131
Dräger Bump Test Station for Dräger X-am® 1/2/5x00, incl. gas cylinder 58L (gas and concentration can be selected)	83 19 130
Nonane tester for Dräger X-am® 1/2/5x00	83 20 080

Communication Accessories

Dräger GasVision	83 14 034
Dräger CC-Vision	Freeware
USB DIRA with USB cable, IR communication adapter to USB	83 17 409
Viton® is a trademark of DuPont.	

CORPORATE HEADQUARTERS

Drägerwerk AG & Co. KGaA
Moislinger Allee 53–55
23558 Lübeck, Germany
www.draeger.com

Manufacturer:

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany

REGION EUROPE CENTRAL AND EUROPE NORTH

Dräger Safety AG & Co. KGaA
Revalstraße 1
23560 Lübeck, Germany
Tel +49 451 882 0
Fax +49 451 882 2080
info@draeger.com

REGION EUROPE SOUTH

Dräger Safety France SAS
25, rue Georges Besse
92182 Antony Cedex
Tel +33 1 46 11 56 00
Fax +33 1 40 96 97 20
europa.south@draeger.com

REGION MIDDLE EAST, AFRICA

Dräger Safety AG & Co. KGaA
Branch Office
P.O. Box 505108
Dubai, United Arab Emirates
Tel +971 4 4294 600
Fax +971 4 4294 699
contactuae@draeger.com

REGION ASIA PACIFIC

Draeger Safety Asia Pte Ltd
25 International Business Park
#04-20/21 German Centre
Singapore 609916
Tel +65 6308 9400
Fax +65 6308 9401
asia.pacific@draeger.com

REGION CENTRAL AND SOUTH AMERICA

Dräger Panama S. de R.L.
Complejo Business Park,
V tower, 10th floor
Panama City
Tel +507 377 9100
Fax +507 377 9130
contactcsa@draeger.com

Locate your Regional
Sales Representative at:
www.draeger.com/contact

