

Lynx™ Rescuer & Dynevac II



- Self Retracting Lanyard with emergency retrieval capabilities.
- User is able to reset device from retrieval mode to fall arrest mode.
- Dynevac II utilises a safety pin feature for field re-set from inertia reel to recovery and back to inertia reel.
- Lynx Rescuer utilises a lock feature with key which allows more control over who can reset the unit back to fall arrest mode.
- Provides fall arrest and emergency lifting and lowering for confined space entry.

PART NO:	Description
10011744	Lynx Rescuer, 16m travel, stainless steel cable
10011745	Lynx Rescuer - 30m travel, stainless steel cable
10007782	Dynevac II, 16m stainless steel cable
10007783	Dynevac II, 30m stainless steel cable

Note: Separate Mounting Bracket (506232 - 16m; 506216 32m), Pulley (506222) and Karabiner (765807) are required for use with Tripod

Rescue Safe Rope Rescue Retrieval System



- For raising and lowering people in rescue and industrial work access and is ideal for confined space applications.
- Overspeed locking brake.
- Hand ascender for aiding the operation and fail safe brake.
- Anchor strap and karabiners (2).
- 3:1 or 4:1 mechanical advantage.

PART NO:	Description
229090-45.0	3:1 Ratio - 45m (Max. Trav - 15m)
229090-60.0	3:1 Ratio - 60m (Max. Trav - 20m)
229090-90.0	3:1 Ratio - 90m (Max. Trav - 30m)
229485-60.0	4:1 Ratio - 60m (Max. Trav - 15m)
229485-80.0	4:1 Ratio - 80m (Max. Trav - 20m)
229485-120.0	4:1 Ratio - 120m (Max. Trav - 30m)